



Denture - Gear - Verzahnung		Tolérances générales suivant IT-ETR-061 et ISO 8015 General tolerances according to IT-ETR-061 and ISO 8015 Allgemeine Toleranzen nach IT-ETR-061 und ISO 8015					Masse estimée — 12 — kg Gewicht ca — — lbs Estimated weight — — lbs	N° 01-0235-00
Droite								Indice B
Module 3 Angle de pression 20° Module - Modul Diámetro pitch Eingriffswinkel Nbre de dents 104 Troncature Truncature - Kopfkürzung Pitch diameter - Teilkreissdurchmesser 312 Report 2 nd Add. mod 2 m d - Profilverschiebung 2 m d Cote sur 13 dents 114.923 Measurement on teeth 114.824 Zahmensweite bei Zähnen		X	R.E. O.R A.R.	20	Trous de fixation Ø 13.50 Mounting holes Befestigungsboreungen	equiv. equiv. gl. Abst.		Des. _____ Date. _____ Ver. _____ Data. _____ Ech. _____
			R.I. I.R I.R.	20-1	Trous de fixation M12 Mounting holes Befestigungsboreungen	equiv. equiv. gl. Abst.		
		G	R.E. O.R A.R.	2	Trous de graisseurs M 6 x 1.00 Grease holes Schmierboeren	equiv. equiv. gl. Abst.		
			R.I. I.R I.R.	2	Trous de graisseurs M 6 x 1.00 Grease holes Schmierboeren	equiv. equiv. gl. Abst.		
		B	Position approximative du bouchon et du raccord de trempe Filler plug and hardening connection of raceway ca Stopfen - und heerteschlupf - position					
		R						
Non trempée No hardened Ungehartet 0.29								
Trempée Hardened Gehartet 0.39								Add: No.3 Lianmeng road, Luoyang, Henan, China. Postal: 471003 Phone: +86-379-68611678 Fax: +86-379-68611679 E-mail: sales@jcb-bearing.com