



Ø 770 f9

Ø 736

Diamètre moyen Ø 673

Ø 17.50

55

0 541

Ø 552

0 575 H9

Ø 610

Ansicht nach A




11° 15'

R

B

BR



Des.

Date. _____

Ver. _____

Date. _____

Ech. _____

Nº	07-0673-00
----	------------

Indice	<u>A</u>
--------	----------

Luoyang JCB Bearing Technology Co., Ltd

Add: No.3 Lianmeng road,Luoyang,Henan,China.

Postal: 471003

Phone: +86-379-68611678

Fax: +86-379-68611679

E-mail: sales@jcb-bearing.com

Tolérances générales suivant IT-ETN-061				
General tolerances according to IT-ETN-061				
Allgemeine toleranzen nach IT-ETN-061				
X	B.E. O.R. A.R.	32	Trous de fixation Mounting holes Befestigungsboreungen	Ø 17.50 equiv. equiv. gl. Abst.
	B.I. I.R. I.R.	32	Trous de fixation Mounting holes Befestigungsboreungen	Ø 17.50 equiv. equiv. gl. Abst.
	B.E. O.R. A.R.	4	Trous de graisseurs Grease holes Schmierboeren	M 10 x 1.00 equiv. equiv. gl. Abst.
	B.I. I.R. I.R.		Trous de graisseurs Grease holes Schmierboeren	equiv. equiv. gl. Abst.
G				
B	Position approximative du bouchon et du raccord de trempe			
R	Filler plug and hardening connection of raceway ca Stopfen - und heerteschlupf - position			

	Masse estimée _____ g Gewicht ca _____ kg Estimated weight _____ lbs
	Des. _____ Date. _____ Ver. _____ Date. _____ Ech. _____