




Denture - Gear - Verzahnung		Tolérances générales suivant IT-ETR-061 et ISO 8015 General tolerances according to IT-ETR-061 and ISO 8015 Allgemeine toleranzen nach IT-ETR-061 und ISO 8015				Masse estimée Gewicht ca Estimated weight 270 kg lbs	N° 08-0823-08
Module _____ Angle de pression _____ Module - Modul _____ Pressure angle _____ Diametral pitch _____ Eingriffswinkel _____ Nbre de dents _____ Troncature _____ Nr. of teeth - Zahnezahl _____ Truncature - Kopfkürzung _____ Diamètre primitif _____ Pitch diameter - Teilkreissdurchmesser _____ Add. 2 m d _____ Profilverschiebung 2 m d _____ Cote sur dents _____ Measurement on teeth _____ Zahnmesbreite bei Zähnen _____ Pour rond au diamètre primitif - Run out on P.D. Rundlauffehler am Teilkreis _____		X B.E. 36 Trous de fixation Ø 22 equid. O.R. Mounting holes equis. A.R. Befestigungsborengen gl. Abst. B.I. 36-1 Trous de fixation Ø 22 equid. I.R. Mounting holes equis. I.R. Befestigungsborengen gl. Abst. G B.E. 4 Trous de graisseurs M 10 x 1.00 equid. O.R. Grease holes equis. A.R. Schmierborengen gl. Abst. B.I. 4 Trous de graisseurs M 10 x 1.00 equid. I.R. Grease holes equis. I.R. Schmierborengen gl. Abst.					
Non trempée _____ No hardened _____ Ungehartet _____ Trempée _____ Hardened _____ Gehartet _____		B Position approximative du bouchon et du raccord de trempé R Filler plug and hardening connection of raceway ca Stopfen - und heerteschlupf - position				Indice A Luoyang JCB Bearing Technology Co., Ltd Add: No.3 Lianmeng road, Luoyang, Henan, China. Postal: 471003 Phone: +86-379-68611678 Fax: +86-379-68611679 E-mail: sales@jcb-bearing.com	