

# Luoyang Jiecheng Bearing Technology Co., Ltd

## Catalog of self-aligning ball bearing

Add: D1805, No.3 Lianmeng road, Luoyang, Henan,China.

Postal: 471003

Phone: +86-379-68611678

Fax: +86-379-68611679

E-mail: sales@jcb-bearing.com

Bearing No.	Specification (mm)			Weight (kg)
	Outer diameter	Inner diameter	Width	
1018	22	8	7	0.015
1026	9	6	6	0.01
1027	22	7	7	0.015
1029	26	9	8	0.023
1200	30	10	9	0.035
1201	32	12	10	0.042
1202	35	15	11	0.051
1203	40	17	12	0.076
1204	47	20	14	0.12
1204K	47	20	14	0.12
1205	52	25	15	0.14
1205K	52	25	15	0.14
1206	62	30	16	0.23
1206K	62	30	16	0.23
1207	72	35	17	0.32
1207K	72	35	17	0.32
1208	80	40	18	0.42
1208K	80	40	18	0.42
1209	85	45	19	0.49
1209K	85	45	19	0.49
1210	90	50	20	0.55
1210K	90	50	20	0.55
1211	100	55	21	0.72
1211K	100	55	21	0.7
1212	110	60	22	0.89
1212K	110	60	22	0.877
1213	120	65	23	0.92
1213K	120	65	23	0.91
1214	125	70	24	1.29
1214K	125	70	24	1.26
1215	130	75	25	1.35
1216	140	80	26	1.6
1216K	140	80	26	1.59
1217	150	85	28	2.1

Bearing No.	Specification (mm)			Weight (kg)
	Outer diameter	Inner diameter	Width	
1218	160	90	30	2.44
1218K	160	90	30	2.4
1219	170	95	32	3.06
1219K	170	95	32	3.02
1220	180	100	34	3.7
1220K	180	100	34	3.67
1221	190	105	36	4.71
1222	200	110	38	5.33
1001228H	250	140	50	11.3
1300	35	10	11	0.06
1301	37	12	12	0.07
1302	42	15	13	0.099
1303	47	17	14	0.138
1304	52	20	15	0.174
1305	62	25	17	0.26
1305K	62	25	17	0.26
1306	72	30	19	0.39
1306K	72	30	19	0.39
1307	80	35	21	0.54
1307K	80	35	21	0.52
1308	90	40	23	0.71
1308K	90	40	23	0.7
1309	100	45	25	0.962
1309K	100	45	25	0.95
1310	110	50	27	1.21
1310K	110	50	27	1.21
1311	120	55	29	1.58
1312	130	60	31	1.96
1312K	130	60	31	1.96
1313	140	65	33	2.38
1313K	140	65	33	2.36
1314	150	70	35	3.19
1314K	150	70	35	2.9
1315	160	75	37	3.55
1315K	160	75	37	4.48
1316	170	80	39	4.19
1316K	170	80	39	4.19
1317	180	85	41	4.95
1317K	180	85	41	4.88
1318	190	90	43	5.99
1318K	190	90	43	5.5
1319	200	95	45	6.98
1319K	200	95	45	6.98

Bearing No.	Specification (mm)			Weight (kg)
	Outer diameter	Inner diameter	Width	
1320K	215	100	52	8.64
1322	240	110	55	12
1322K	240	110	55	11.9
2200	30	10	14	0.112
2201	32	12	14	0.116
2202	35	15	14	0.118
2203	40	17	16	0.121
2204	47	20	18	0.152
2205	52	25	18	0.187
2205K	52	25	18	0.16
2206	62	30	20	0.26
2206K	62	30	20	0.254
2207	72	35	23	0.441
2207K	72	35	23	0.4
2208K	80	40	23	0.519
2209	85	45	23	0.553
2209K	85	45	23	0.55
2210	90	50	23	0.618
2210K	90	50	23	0.6
2211	100	55	25	0.824
2211K	100	55	25	0.82
2212	110	60	28	1.16
2212K	110	60	28	1.09
2213	120	65	31	1.5
2213K	120	65	31	1.46
2214	125	70	31	1.63
2214K	125	70	31	1.62
2215	130	75	31	1.71
2215K	130	75	31	1.62
2216	140	80	33	2.19
2216K	140	80	33	2
2217	150	85	36	2.53
2217K	150	85	36	2.48
2218	160	90	40	3.22
2218K	160	90	40	3.16
2219	170	95	43	4.2
2219K	170	95	43	4.1
2220	180	100	46	4.61
2220K	180	100	46	4.6
2222	200	100	53	7.16
2222K	200	100	53	7
2303	47	17	19	0.19
2304	52	20	21	0.219

Bearing No.	Specification (mm)			Weight (kg)
	Outer diameter	Inner diameter	Width	
2305K	62	25	24	0.35
2306K	72	30	27	0.52
2307	80	35	31	0.68
2307K	80	35	31	0.66
2308	90	40	33	0.96
2308K	90	40	33	0.94
2309	100	45	36	1.3
2309K	100	45	36	1.23
2310	110	50	40	1.66
2310K	110	50	40	1.65
2311	120	55	43	2.09
2311K	120	55	43	2.05
2312	130	60	46	2.58
2312K	130	60	46	2.49
2313	140	65	48	3.22
2313K	140	65	48	3.21
2314	150	70	51	3.92
2314K	150	70	51	3.92
2315	160	75	55	4.71
2315K	160	75	55	4.63
2316	170	80	58	5.7
2316K	170	80	58	5.55
2317	180	85	60	6.73
2317K	180	85	60	6.56
2318	190	90	64	8.27
2318K	190	90	64	7.8
2319	200	95	67	9.16
2319K	200	95	67	9.16
2320	215	100	73	12.4
23220K	215	100	73	12.4
2200-2RS	30	10	14	0.112
2201-2RS	32	12	14	0.116
2202-2RS	35	15	14	0.118
2203-2RS	40	17	16	0.121
2204-2RS	47	20	18	0.152
2205-2RS	52	25	18	0.187
2206-2RS	62	30	20	0.26
2207-2RS	72	35	23	0.441
2208-2RS	80	40	23	0.519
2209-2RS	85	45	23	0.55
2210-2RS	90	50	23	0.618
2211-2RS	100	55	25	0.824
2212-2RS	110	60	28	1.16

Bearing No.	Specification (mm)			Weight (kg)
	Outer diameter	Inner diameter	Width	
2303-2RS	47	17	19	0.19
2304-2RS	52	20	21	0.219
2305-2RS	62	25	24	0.355
2306-2RS	72	30	27	0.52
2307-2RS	80	35	31	0.68
2308-2RS	90	40	33	0.96
2309-2RS	100	45	36	1.3
2310-2RS	110	50	40	1.66