

Luoyang Jiecheng Bearing Technology Co., Ltd

Tel:0086-379-68611678 Fax:0086-379-68611679 Email:

sales@jcb-bearing.com

Thrust tapered roller bearing

Dimensions			Basic rated Load		fatigue load limiting value	Least load coefficient	Mass	Bearing No.
d	D	H	C	C0				
mm			kN		kN			
220	500	125	3580	16000	965	20	160	351148 B
228,6	482,6	104,775	3300	15000	915	18	100	K-T 911
234,95	546,1	127	4570	21600	1200	37	165	K-T 921
260	580	145	4680	21200	1220	36	210	351153
279,4	603,25	136,525	7210	28500	1800	65	205	BFSB 353316/HA7
279,4	603,25	136,525	5390	26000	1430	54	205	K-T 1120
300	660	165	5940	27000	1500	58	350	351195
300	663,5	165	6600	28000	1730	63	315	BFSB 353916
340	460	73	1230	5700	400	2,6	37,0	BFSB 350565
347,5	710	160	7810	40000	2280	130	345	351468 A
370	560	115	3520	14300	1040	16	110	BFSB 353205
380	560	110	2860	12000	830	12	110	353164
480	730	112	3580	19000	1180	29	180	350998
500	760	140	5940	30500	1800	74	250	BFS 8000/HA1
558,8	1066,8	285,75	19800	75000	4150	450	1200	BFSB 353285/HA4
600	900	170	7040	32500	1900	84	405	BFSB 353201
749,3	952,5	127	5830	30000	1730	72	230	BFSB 353247
840	1140	195	11200	64000	3400	330	575	351573
1002	1274	150	8970	57000	3000	260	465	BFSB 353901/HA4
1005	1280	150	8250	51000	2650	210	505	BFSB 353210
1770	1930	80	3300	32000	1400	82	250	BFSB 353312/HA1
1828,8	2184,4	203,2	20500	143000	6200	1600	1450	BFSB 353320/HA4